



# DJ Lead-Calcium Battery

**FOR SWITCHGEAR & CONTROL APPLICATIONS**  
Capacities from 110 to 200 Ampere-hours



Every cell  
**100%**  
capacity tested

DJ SERIES BATTERY

C&D Technologies' flooded batteries are engineered to provide superior performance and reliability over the life of the product. These batteries are designed using proprietary techniques and quality components and materials for reduced maintenance and extended battery life.

## APPLICATIONS

- Electric Utility Substations
- Manufacturing Facilities
  - Assembly Lines
  - Process Controls
  - Communication Systems
- Petrochemical Processing Plants
- Pipelines
- Emergency Systems

## FEATURES & BENEFITS

### RELIABILITY

- Time tested epoxy post seal and reliable tongue and groove jar-to-cover seal designs provide increased adhesive coverage area — offering unprecedented seal integrity during service
- Top suspended positive plate design allows free downward growth without pressure on jar, cover, or post seal — extending reliability and product life
- Recessed vent area to collect water and acid spills, keeping them away from posts and cover — lowering maintenance and clean-up costs
- Wrapped separator design extends cycle life — improving product reliability
- Enhanced post seal design

### SAFE OPERATION

- Self extinguishing features (LOI >32) of flame retardant (FR) cover and jar material — providing added protection
- Low evaporation, flame arrestor vents protect against external source from igniting hydrogen gas within the cells — improving safety

### COST SAVINGS

- Unique jar design facilitates installation
- Compact, optimized product size nets up to 40% floor space reduction — saving valuable space
- Angled posts use standard lead-plated copper connectors and improved post to connector contact — lowering resistance and allowing for quicker installation

The new 20-year design life DJ batteries incorporate these benefits in a transparent container for visual inspection of plates and individual cell voltage taps on the connector covers for cell voltage readings.

## SPECIFICATIONS

<b>Recommended float voltage range</b>	2.20–2.25 volts per cell (1.215 specific gravity)
<b>Specific gravity of electrolyte @77°F (25°C)</b>	1.215 (standard)
<b>Cover material – Standard</b>	High impact, PVC, LOI>32, UL94-V0
<b>Container material – Standard</b>	Transparent, high-impact PVC, LOI>32, UL94-V0
<b>Separator material – Standard</b>	U-wrapped, microporous with fibrous mat
<b>Terminal type</b>	Hardened lead post
<b>Safety vent</b>	Flame arrestor / low evaporation type

C&D capacity tests every DJ battery to 100% of published rating which ensures 100% capacity out-of-the-box (no need to field cycle the batteries to reach rated capacity). This saves time and money for users.

## SPECIFICATIONS

Nominal rates 1.215 specific gravity @ 77°F (25°C) (includes connector voltage drop) \*  
Amperes

Models	FV/Cell	1 min	15 min	30 min	1 hr	2 hr	3 hr	4 hr	5 hr	8 hr	12 hr
DJ-110	1.75	158.1	117.4	87.9	59.6	37.9	28.3	22.9	19.5	13.8	9.9
	1.78	139.3	105.0	80.1	55.5	35.9	27.0	22.1	18.8	13.3	9.7
	1.81	120.5	92.6	72.4	51.4	33.9	25.8	21.2	18.2	12.9	9.4
	1.85	94.9	78.2	62.4	44.8	30.6	23.9	19.8	17.0	12.1	8.8
DJ-155	1.75	226.3	168.0	125.8	85.4	54.3	40.5	32.8	27.9	19.5	14.2
	1.78	199.5	150.3	114.7	79.5	51.4	38.7	31.6	26.9	19.0	13.8
	1.81	172.6	132.5	103.6	73.6	48.5	37.0	30.4	26.0	18.5	13.5
	1.85	135.9	112.0	89.4	64.2	43.8	34.2	28.4	24.4	17.3	12.6
DJ-200	1.75	287.4	213.4	159.8	108.4	68.9	51.4	41.7	35.4	25.0	18.0
	1.78	253.3	190.8	145.7	100.9	65.3	49.2	40.2	34.2	24.1	17.6
	1.81	219.2	168.3	131.5	93.5	61.6	47.0	38.6	33.0	23.4	17.1
	1.85	172.6	142.2	113.5	81.5	55.6	43.5	36.1	31.0	22.0	15.9

Additional ratings and application information is available in the Battery Selection Program @ [www.cdstandbypower.net](http://www.cdstandbypower.net)

Note: Data based discharge from float at 77°F (25°C) in accordance with IEEE-450

## SPECIFICATIONS

Type of battery	Part number	Cells per unit	Plates per cell	Overall dimensions			Approx. wt. lbs (kgs)		Electrolyte per cell gal. (l)
				L in (mm)	W in (mm)	H in (mm)*	Net filled	Dom. packed	
3DJ-110	CW17784-PVC	3	5	8.09 (205.5)	13.58 (344.9)	15.22 (386.6)	101 (46)	112 (51)	1.23 (4.66)
3DJ-155	CW17785-PVC	3	7				120 (54)	131 (59)	1.09 (4.13)
3DJ-200	CW17786-PVC	3	9				139 (63)	150 (68)	0.95 (3.60)
2DJ-110	CW17787-PVC	2	5				71 (32)	82 (37)	1.23 (4.66)
2DJ-155	CW17788-PVC	2	7				83 (38)	94 (43)	1.09 (4.13)
2DJ-200	CW17789-PVC	2	9				96 (44)	107 (49)	0.95 (3.60)

\* 2 cells in a 3 cell jar. Use with 3 cell jars to obtain correct voltage.

## DJ RACK SELECTION MATRIX

	Non-seismic racks			Seismic racks		
	1 Tier, 1 Row	2 Tier, 1 Row	2 Step	1 Tier, 1 Row	2 Tier, 1 Row	2 Step
48 V (8 Jars)	RDB0800-06P	RDB0801-03P	RDB0803-03P	RDB0800-06EP1P RDB0800-06EP2P	RDB0801-03EP1P RDB0801-03EP2P	RDB0803-03EP1P RDB0803-03EP2P
120 V (20 Jars)	RDB0800-15P	RDB0801-7.3P	RDB0803-7.3P	RDB0800-15EP1P RDB0800-15EP2P 7.3EP2P	RDB0801-7.3EP1P RDB0801-7.3EP2P	RDB0803-7.3EP1P RDB0803-

3 Tier, 1 Row racks are also available.

## C&D TECHNOLOGIES, INC.

1400 Union Meeting Road  
P.O. Box 3053 • Blue Bell, PA 19422-0858  
(215) 619-2700 • Fax (215) 619-7899 • (800) 543-8630  
[customersvc@cdtechno.com](mailto:customersvc@cdtechno.com)  
[www.cdtechno.com](http://www.cdtechno.com)

Any data, descriptions or specifications presented herein are subject to revision by C&D Technologies, Inc. without notice. While such information is believed to be accurate as indicated herein, C&D Technologies, Inc. makes no warranty and hereby disclaims all warranties, express or implied, with regard to the accuracy or completeness of such information. Further, because the product(s) featured herein may be used under conditions beyond its control, C&D Technologies, Inc. hereby disclaims all warranties, either express or implied, concerning the fitness or suitability of such product(s) for any particular use or in any specific application or arising from any course of dealing or usage of trade. The user is solely responsible for determining the suitability of the product(s) featured herein for user's intended purpose and in user's specific application.